


双列滚珠轴承

内径 10~75mm



| 主要寸法(mm) | | | | 基本型號 | 基本定格荷重(kgf) | | 極限速率(rpm) | |
|----------|-----|------|-----|------|-------------|------|-----------|-------|
| d | D | B | r | | C | Co | 脂潤滑 | 油潤滑 |
| 10 | 30 | 14.3 | 1 | 5200 | 545 | 345 | 14000 | 19000 |
| 12 | 32 | 15.9 | 1 | 5201 | 715 | 465 | 13000 | 17000 |
| 15 | 35 | 15.9 | 1 | 5202 | 785 | 535 | 11000 | 15000 |
| | 42 | 19 | 1.5 | 5302 | 1130 | 775 | 9900 | 13000 |
| 17 | 40 | 17.5 | 1 | 5203 | 1000 | 700 | 9900 | 13000 |
| | 47 | 22.2 | 1.5 | 5303 | 1000 | 1160 | 9000 | 12000 |
| 20 | 47 | 20.6 | 1.5 | 5204 | 1540 | 1170 | 8800 | 12000 |
| | 52 | 22.2 | 2 | 5304 | 1930 | 1450 | 8000 | 11000 |
| 25 | 52 | 20.6 | 1.5 | 5205 | 1670 | 1330 | 7300 | 9800 |
| | 62 | 25.4 | 2 | 5305 | 2560 | 1980 | 6700 | 8900 |
| 30 | 62 | 23.8 | 1.5 | 5206 | 2320 | 1920 | 6300 | 8400 |
| | 72 | 30.2 | 2 | 5306 | 3200 | 2630 | 5700 | 7600 |
| 35 | 72 | 27 | 2 | 5207 | 3000 | 2620 | 5500 | 7400 |
| | 80 | 34.9 | 2.5 | 5307 | 4050 | 3400 | 5000 | 6600 |
| 40 | 80 | 30.2 | 2 | 5208 | 3450 | 3000 | 4900 | 6600 |
| | 90 | 36.5 | 2.5 | 5308 | 4950 | 4250 | 4400 | 5900 |
| 45 | 85 | 30.2 | 2 | 5209 | 3900 | 3450 | 4400 | 5900 |
| | 100 | 39.7 | 2.5 | 5309 | 5850 | 5150 | 4000 | 5300 |
| 50 | 90 | 30.2 | 2 | 5210 | 4150 | 3850 | 4000 | 5300 |
| | 110 | 44.4 | 3 | 5310 | 7450 | 6750 | 3600 | 4800 |
| 55 | 100 | 33.3 | 2.5 | 5211 | 5150 | 4900 | 3600 | 4900 |
| | 120 | 49.2 | 3 | 5311 | 8600 | 7950 | 3300 | 4400 |
| 60 | 110 | 36.5 | 2.5 | 5212 | 6200 | 6000 | 3400 | 4500 |
| | 130 | 54 | 3.5 | 5312 | 9800 | 9150 | 3000 | 4000 |
| 65 | 120 | 38.1 | 2.5 | 5213 | 6750 | 6650 | 3100 | 4200 |
| 70 | 125 | 39.7 | 2.5 | 5214 | 7350 | 7300 | 2900 | 3900 |
| 75 | 130 | 41.3 | 2.5 | 5215 | 7750 | 8050 | 2700 | 3600 |